


H2R说明书尺寸: 65*90mm
正反16面 7折 英文朝上

[illegible]



Carbon

Portable Steady Beam Searchlight


User Manual

Specifications

OUTPUT (lumens)	ECO	LOW	MED	HIGH	TURBO	STROBE	SOS
MAXIMUM	30	30	150	600	2000	3000	150
RUNTIME (hours)	2000	1700	50	14	4	8	1000
BEAM DISTANCE (meters)	17	57	320	200	450	/	/
INTENSITY (lux)	72	82	3660	1225	5505	/	/
IMPACT RESISTANCE	1 Meters						
SUBMERSIBLE	#30ft/meters underwater						
SIZE	184mm(7.2in)X4.8mm						
WEIGHT	288g (10.16oz) battery						
WORKING TEMPERATURE	-30°C/-55°C/22°F/-43°F						
CHARGING VOLTAGE RANGE	4.2V ~ 4.65V						
BATTERY COMPATIBILITY	This product comes equipped with the CR1632 battery, other batteries are not compatible.						

Note: The data above is based on the ANSI / ILLUMINANCE standard using a C14000 (1000mAh 3621) lithium ion phosphate battery at 25°C/77°F and 50%-90% humidity, tested in the CYANSKY laboratory environment. Actual performance may vary with battery and usage conditions. The overall endurance time refers to the total duration of the smart dimming test.

Discharging Curve



Operating Instruction

Power On/Off: Single click the button to turn on/off. When turned on, remember the last used mode (only LOW/MED/HIGH modes). Battery level for 3 seconds when turned on.

Adjust Brightness: Long press the button to cycle through LOW > MED > HIGH, release to select brightness.

ECO: Long press the button while the flashlight is off.


TURBO: Double-click to enter TURBO (brightness decreases gradually based on battery voltage and temperature).

STROBE: Triple-click to enter STROBE, click once or long press to exit.

SOS: In STROBE, triple-click to enter SOS; click once or long press to exit.


Lock/Unlock: Four or more quick clicks to lock/unlock. (Low Mode flashes twice to indicate status).

Product Illustration



Smartly Reduce Brightness: To ensure lighting safety, the product will intelligently reduce the brightness in the following situations: - Automatic brightness reduction to low mode when battery is low. - If the product temperature is higher than the safe value (50°C), the brightness of the product will be reduced through temperature control to avoid product damage and injury to users. **Low Battery Warning:**

Battery Level Indicator



Charging:

Insert the charging cable. Green light indicates full charge (about 4 hours to full).

Discharging:

LED indicator goes off from right to left when discharging (about full after charge).

Precautions:

- Different charging protocols support different currents. The voltage platform of lithium ion phosphate batteries 3.65V. Charging to extend device services when the battery voltage is below 3.0V (about 50% battery).
- It is recommended to use the original Canon charging cable for charging/discharging.
- When using C to C to A adapter, please choose one with OTG function.
- If other C-C charging cables or adapters cannot charge, try inserting the charging cable in the opposite direction.
- When charging on iPhone, please use the original Apple charging cable.

Caution

- Do not connect battery positively and negative terminals backward.
- Please fully charge the battery before first use.
- Children must use this product under adult supervision.
- Do not put the product with opened cover into water.
- Do not put the product with the battery into the fire. Otherwise, it will explode.
- The product has high brightness, flashlight does not look directly at the face, birds, etc. it may cause eye damage and temporary blindness.
- Please remove the batteries when the product is left unused.
- When carrying, please turn the battery cover loose half a turn to let the product power off to avoid mistakenly lighting up while carrying.
- When using an external power supply to power the Canon lamp head (without the body and battery), the light may enter or flicker or low settings. This is because the fast charging chip is detecting, which is a normal phenomenon.

Warranty Terms

For the first 15 days from the date of sale, if there is a product quality problem under normal use, customers can choose to replace it with a new product of the same model and specification. If the product of the same model and specification has been discontinued, it will be replaced with a product of the same brand and class with no lower performance.

5-year free warranty period from the date of sale, the lamp product has a free warranty period of 5 years (1 year for batteries). If there is a product quality problem under

normal use, the user can enjoy free repair service. After 5 years, paid repair service will be provided, only cost fees will be charged.

When consumer seeks warranty service, they should contact the dealer with the "Warranty Card", shopping invoice or receipt, or the code provided by the online retailer, and the dealer will provide service to the user. Our company will provide service to the dealer.

Warranty service does not include any damage or malfunction caused by the following reasons:

- Dropping from high altitude, modification or alteration without permission.
- Damage caused by rough or mistaken operation.
- Damage caused by improper use, storage or maintenance.
- Normal wear and tear.
- Battery leakage.
- Corrosion of the unit caused by saltwater.
- Ordinary wear/tearing.

Certifications

CE, FCC, FCC, RoHS 2.0, UKCA, sea/air safe transport.

Website: <https://www.cyanskylight.com>

Email: info@cyanskylight.com

Phone: +86-759-8292209

Address: 601 2nd Building, Xiangdong Technopark, 781000 Ninghai County Road, Dapingshan Town, Dongshangmen, 523000, China

